

TARMIL

ASPHALT

Gaston MILLE®

SPECIAL HAZARDS

GASTON MILLE



HRO UP TO 300°C	♂	39/47	FIBERGLASS 240J	TEXTILE 1430N
0% METAL FREE	SBP	MESH-LINING	1,26KG	



HIGHLIGHTS HRO PU Nitrile non marking smooth outsole

SAFETY LEVEL STANDARDS

SBP WRU HI HRO
EN ISO 20345:2011

COMPOSITION



Safety toe-cap
(resistant up to 240J)



Penetration-resistant midsole
(resistant up to 1 430N)



Non marking smooth outsole

A

Antistatic footwear

E

Energy absorption in the heel region

FO

Fuel Oil resistant outsole

WRU

Water resistant upper

HI

Insulation against Heat

HRO

Heat Resistant Outsole 300°C

Upper	Full grain leather water & oil resistant
Lining	Mesh-lining: ventilated + antibacterial + abrasion resistant
Toe-cap	Composite (fiberglass)
Footbeds	Removable + antibacterial + HRO Soft (aluminium)
Penetration Resistant midsole	Textile
Sole	PU/Nitrile rubber resisting up to 300°C
Net weight/pair (size 42)	1 260g
Sizes	39-47 / 6-13
Item code	RNNG3
Feature	Non marking smooth outsole for hot asphalt floors - roadworks

* SRA: Slipping resistance on ceramic tile wet with soap solution

** SRB: Slipping resistance on smooth steel with glycerol

MILLE SAS • 69 Rue Marcel Valérien - 84350 Courthézon - France • Tel. +33(0) 4 90 70 40 40 • Email: welcome@gastonmille.fr • www.gastonmille.com

The product specifications & performances are guaranteed only if Gaston Mille footbeds are worn. MILLE SAS may modify the specifications of the product manufacture.