





TARMIL

ASPHALT

Gaston **MILLE**[®]

SPECIAL HAZARDS

HRO UP TO 300°C	♂	39/47	 FIBERGLASS 240J	 TEXTILE 1430N
0% METAL FREE	SBP	 MESH-LINING	 1,631KG	



HIGHLIGHTS HRO PU Nitrile non marking smooth outsole

SAFETY LEVEL STANDARDS

SBP E FO WRU HI HRO
EN ISO 20345:2011



Safety toe-cap
(resistant up to 240J)



Penetration-resistant midsole
(resistant up to 1 430N)



Non marking smooth outsole

A

Antistatic footwear

E

Energy absorption in the heel region

FO

Fuel Oil resistant outsole

WRU

Water resistant upper

HI

Insulation against Heat

HRO

Heat Resistant Outsole 300°C

COMPOSITION

Upper	Full grain leather water & oil resistant
Lining	Mesh-lining: ventilated + antibacterial + abrasion resistant Sanitized [®]
Toe-cap	Composite (fiberglass)
Footbeds	Removable + antibacterial + HRO Soft (aluminium)
Penetration Resistant midsole	Textile
Sole	PU/Nitrile rubber resisting up to 300°C
Net weight/pair (size 42)	1 631g
Sizes	39-47 / 6-13
Item code	RNHP3
Feature	Non marking smooth outsole for hot asphalt floors - roadworks

* SRA: Slipping resistance on ceramic tile wet with soap solution

** SRB: Slipping resistance on smooth steel with glycerol

GASTON MILLE