

# UNITAN

Ref. UOMA3

EN ISO 20345 : 2022 S3 HI CI FO LG SR



#### **LONG LASTING - ECO-FRIENDLY**

For more than 110 years, Gaston MILLE has been improving safety footwear by limiting its impact on the environment and by choosing quality materials that are more sustainable and eco-responsible.



### **UPPER**

Full grain leather (2 to 2.2mm thick), water and oil repellent, strong, supple and long lasting - all our leathers are selected with great care. No side stiches for greater sturdiness.

Sides grip loops for easy on and off.

Cushioned and soft upper for more flexilibility and comfort to avoir overheating.

Retroreflective strip for better visibility on construction sites and roadsides.

Wide opening at the back of the boot for easy on/off.

#### LARGE PROTECTIVE TOE CAP

Fiberglass (10% lighter than steel with superior strength), athermic & non-magnetic. Comfort skirt: plastic extension to avoid feeling the toe cap when bending the foot.

#### **ANTI-PUNCTURE SOLE**

Stainless steel penetration-resistant midsole

#### LINING

Sanitized® lining => the Sanitized hygiene function protects from the formation of funqi and provides long-lasting protection.

Fast evaporation, allowing to feel drier and cooler, with temperature regulation. Good resistance to abrasion.

Back reinforcement: avoids overheating due to friction.

#### **REMOVABLE & ANATOMICAL INSOLE**

Mille Soft®, ultra thick PU foam (1.5 cm) for optimum comfort, ergonomic, moisture absorption, good breathability, anti-abrasion and anti-fungal, washable at 30°C.

Arch support, shock absorption in the heel area, soft optimal comfort. Possibility to insert an **orthopedic insole.** 

#### **EXTRA-LARGE STUDDED OUTSOLE**

PU/PU - excellent shock absorb + grip on all types of ground, optimal stability, abrasion resistance of external toe cap reinforcements (stone guard)

#### **UPPER HEIGHT**

29 cm

#### WEIGHT

1,640 Kg (net for 1 pair size 43)

## ITEM CODE - SIZES

UOMA3 - from 37 to 48 - US sizes 6 to 13

#### RANGE

1912 - This reference is designed to stand the test of time in the respect of the normative requirements and comfort.

#### USE

Outdoor, construction, agriculture, green spaces, extreme and difficult conditions, risky industrial environments (mines), special hazards, heavy industry (oil platform), harsh outdoor environments (specific soils; ballast...)









## UNITAN



### **COMFORT SOLE FUSIONGRIP®**

Ultra-light Polyurethane with high energy return (64%) - High Rebound.

#### **OUTSOLE FUSIONGRIP®**

Polyurethane - 4 mm outsole resistant to abrasion, cuts, hydrocarbons, chemicals and acids.

Sharp studs to improve grip on all types of ground - rough, rocky, unsteady, muddy or slippery surfaces.

- (1) Liquid evacuation on the sides to prevent aquaplaning
- (2) 1 cm deep for better grip on ladder rungs
- Turbo Flex System®: anti-torsion arch support
- (4) Shock Absorb®: shock absorption in the heel to protect the back and joints anti-fatique effect
- 7 mm high profiled studs for better grip
- (6) Ridges on the front and back to prevent slipping
- (7) Large, spaced, flexible studs to prevent grit from getting stuck self-cleaning sole
- (8) Flex zone no discomfort to the natural rolling of the foot

#### **SPECIFICATIONS**

Large contact area for improved stability and maximum grip. Generous, wide fit for long-lasting comfort.

#### **COMPLIANCE**

- SB Basic requirements (innocuousness, strength, resistance to shock hazards & compression : 200 J)
- **A** Antistatic shoe
- **E** Energy absorption in the heel region
- **FO** Fuel Oil resistant sole
- WPA Water Penetration & Absorption Resistant
  Penetration resistant sole (metallic)
- **LG** Grip on ladders
- HI Insulation of the sole against Heat
  CI Insulation of the sole against Cold
- **LG** Grip on Ladders
- SR High performance grip. Slip Resistant outsole on ceramic tile wet with soap solution and on smooth steel with glycerol (oil)

The properties of the product remain unchanged only if insoles the manufacturer's recommended are used.

Mille SAS reserves the right to modify the manufacturing characteristics of its products without notice. Document and photos are not contractual.





