

# **UNION**

Ref. UHMA3

EN ISO 20345 : 2022 S3 HI CI FO LG SR





#### **LONG LASTING - ECO-FRIENDLY**

For more than 110 years, Gaston MILLE has been improving safety footwear by limiting its impact on the environment and by choosing quality materials that are more sustainable and eco-responsible.

### **UPPER**

Nubuck leather (2 to 2.2mm thick), water and oil repellent, strong, supple and long lasting - all our leathers are selected with great care. Tongue with waterproof gussets to prevent dust and liquids from entering.

No side stiches for greater sturdiness.

Cushioned and soft upper for more flexilibility and comfort to avoid overheating.

Rear grip loop for easy on and off.

Perforations on the side for better ventilation of the product.

#### LARGE PROTECTIVE TOE CAP

Fiberglass (10% lighter than steel with superior strength), athermic & non-magnetic. Comfort skirt: plastic extension to avoid feeling the toe cap when bending the foot.

# ANTI-PUNCTURE SOLE

Stainless steel penetration-resistant midsole

#### LINING

Sanitized® lining => the Sanitized hygiene function protects from the formation of fungi and provides long-lasting protection.

Fast evaporation, allowing to feel drier and cooler, with temperature regulation. Good resistance to abrasion.

Back reinforcement: avoids overheating due to friction.

# **REMOVABLE & ANATOMICAL INSOLE**

Mille Soft®, ultra thick PU foam  $[1.5\ cm]$  for optimum comfort, ergonomic, moisture absorption, good breathability, anti-abrasion and anti-fungal, washable at 30°C.

Arch support, shock absorption in the heel area, soft optimal comfort. Possibility to insert an **orthopedic insole.** 

### **EXTRA-LARGE STUDDED OUTSOLE**

PU/PU - excellent shock absorb + grip on all types of ground, optimal stability, abrasion resistance of external toe cap reinforcements (stone guard)

# CLOSURE

Laces slide into rivets for a better fit => loose laces can cause overheating.

### **UPPER HEIGHT**

17 cm

# WEIGHT

1,460 Kg (net for 1 pair size 43)

# **ITEM CODE - SIZES**

UHMA3 - from 39 to 48 - US sizes 6 to 13

#### RANGE

1912 - This reference is designed to stand the test of time in the respect of the normative requirements and comfort.

#### USE

Outdoor, construction, agriculture, green spaces, extreme and difficult conditions, risky industrial environments, special hazards, heavy industry, harsh outdoor environments (specific soils; ballast...)









# UNION



# **COMFORT SOLE FUSIONGRIP®**

Ultra-light Polyurethane with high energy return (64%) - High Rebound.

# **OUTSOLE FUSIONGRIP®**

Polyurethane - 4 mm outsole resistant to abrasion, cuts, hydrocarbons, chemicals and acids.

Sharp studs to improve grip on all types of ground - rough, rocky, unsteady, muddy or slippery surfaces.

- (1) Liquid evacuation on the sides to prevent aquaplaning
- (2) 1 cm deep for better grip on ladder rungs
- Turbo Flex System®: anti-torsion arch support
- Shock Absorb®: shock absorption in the heel to protect the back and joints anti-fatigue effect
- 7 mm high profiled studs for better grip
- (6) Ridges on the front and back to prevent slipping
- (7) Large, spaced, flexible studs to prevent grit from getting stuck self-cleaning sole
- (8) Flex zone no discomfort to the natural rolling of the foot

# **SPECIFICATIONS**

Large contact area for improved stability and maximum grip. Generous, wide fit for long-lasting comfort.

# **COMPLIANCE**

- SB Basic requirements (innocuousness, strength, resistance to shock hazards & compression : 200 J)
- **A** Antistatic shoe
- **E** Energy absorption in the heel region
- **FO** Fuel Oil resistant sole
- WPA Water Penetration & Absorption Resistant
  Penetration resistant sole (metallic)
- **LG** Grip on ladders
- HI Insulation of the sole against Heat
  CI Insulation of the sole against Cold
- SR High performance grip. Slip Resistant outsole on ceramic tile wet with soap solution and on smooth steel with glycerol (oil)

The properties of the product remain unchanged only if insoles the manufacturer's recommended are used.

Mille SAS reserves the right to modify the manufacturing characteristics of its products without notice. Document and photos are not contractual.





